

Олимпиада СПбГУ по информатике 2019/20 учебного года

A	B	C	D	E	F	Sum
100	100	100	20	6	0	326

Task A ()

```
#include <iostream>
#include <algorithm>
#include <vector>
#include <set>
#include <map>
#include <unordered_set>
#include <unordered_map>
#include <cmath>
#include <deque>
#include <queue>
#include <list>

using namespace std;

int main()
{
    int n;
    cin >> n;
    cout << n - 1;
    return 0;
}
```

Task B ()

```
#include <iostream>
#include <algorithm>
#include <vector>
#include <set>
#include <map>
#include <unordered_set>
#include <unordered_map>
#include <cmath>
#include <deque>
#include <queue>
#include <list>

using namespace std;

struct p
{
    double x, y;
};

bool eq(double a, double b)
{
    return (fabs(a - b) < 0.1);
}

double len(p a)
{
    return sqrt(a.x * a.x + a.y * a.y);
}

double scal(p a, p b)
{
    return a.x * b.x + a.y * b.y;
}

double smech(p a, p b)
{
    return a.x * b.y - b.x * a.y;
}

bool check120(p a, p b, p c)
{
    p tmp1, tmp2;
    tmp1.x = a.x - b.x;
    tmp1.y = a.y - b.y;
    tmp2.x = c.x - b.x;
    tmp2.y = c.y - b.y;
    return eq(scal(tmp1, tmp2) / len(tmp1) / len(tmp2), -0.5);
}

int main()
{
    int n;
    cin >> n;
    vector<p> a(n);
    for (auto &i : a)
    {
        cin >> i.x >> i.y;
    }
    if (n == 6)
    {
        for (int i = 0; i < n; ++i)
        {
            for (int j = 0; j < n; ++j)
            {
                for (int k = 0; k < n; ++k)
                {
                    if (i == j || i == k || k == j)
                    {
                        continue;
                    }
                    if (check120(a[i], a[j], a[k]))
                    {

```

```

        cout << a[ i ].x << '\u0020' << a[ i ].y << '\n';
        cout << a[ j ].x << '\u0020' << a[ j ].y << '\n';
        cout << a[ k ].x << '\u0020' << a[ k ].y;
        return 0;
    }
}
}

else
{
    vector<p> tmp(6);
    for (int i = 0; i < n; ++i)
    {
        for (int j = 0; j < n; ++j)
        {
            for (int k = 0; k < n; ++k)
            {
                if (i == j || i == k || k == j)
                {
                    continue;
                }
                if (check120(a[ i ], a[ j ], a[ k ]))
                {
                    tmp[ 0 ] = a[ i ];
                    tmp[ 1 ] = a[ j ];
                    tmp[ 2 ] = a[ k ];
                }
            }
        }
    }
    tmp[ 3 ].x = (tmp[ 2 ].x - tmp[ 1 ].x) * 2 + tmp[ 0 ].x;
    tmp[ 3 ].y = (tmp[ 2 ].y - tmp[ 1 ].y) * 2 + tmp[ 0 ].y;
    tmp[ 4 ].x = (tmp[ 3 ].x - tmp[ 2 ].x) * 2 + tmp[ 1 ].x;
    tmp[ 4 ].y = (tmp[ 3 ].y - tmp[ 2 ].y) * 2 + tmp[ 1 ].y;
    tmp[ 5 ].x = (tmp[ 4 ].x - tmp[ 3 ].x) * 2 + tmp[ 2 ].x;
    tmp[ 5 ].y = (tmp[ 4 ].y - tmp[ 3 ].y) * 2 + tmp[ 2 ].y;
    cout << tmp[ 0 ].x << '\u0020' << tmp[ 0 ].y << '\n';
    cout << tmp[ 1 ].x << '\u0020' << tmp[ 1 ].y << '\n';
    cout << tmp[ 2 ].x << '\u0020' << tmp[ 2 ].y << '\n';
    cout << tmp[ 3 ].x << '\u0020' << tmp[ 3 ].y << '\n';
    cout << tmp[ 4 ].x << '\u0020' << tmp[ 4 ].y << '\n';
    cout << tmp[ 5 ].x << '\u0020' << tmp[ 5 ].y;
}
return 0;
}

```

Task C ()

```
#include <iostream>
#include <algorithm>
#include <vector>
#include <set>
#include <map>
#include <unordered_set>
#include <unordered_map>
#include <cmath>
#include <deque>
#include <queue>
#include <list>
#include <string>

using namespace std;

int levDist(string a, string b, int l, int r)
{
    int j = l, ans = 0, sz = a.size(), lim = sz - (r - l + 1);
    for (int i = 0; i < sz && ans <= lim; ++i)
    {
        if (b[j] != a[i])
        {
            ans++;
        }
        else
        {
            j++;
            if (j > r)
            {
                ans += sz - i - 1;
                break;
            }
        }
    }
    return (ans <= lim);
}

int main()
{
    string s;
    cin >> s;
    int sz = s.size();
    set<char> l;
    for (int i = 0; i < s.size(); i++)
    {
        l.insert(s[i]);
    }
    int n;
    cin >> n;
    int ans = 0;
    for (int i = 0; i < n; ++i)
    {
        string c;
        cin >> c;
        int dl = 0, dr = sz + 1, cz = c.size();
        while (dl != dr - 1)
        {
            int d = (dl + dr) / 2;
            bool yes = false;
            for (int j = 0; j <= cz - d && !yes; j++)
            {
                bool flag = false;
                for (int t = j; t < j + d; t++)
                {
                    if (l.find(c[t]) == l.end())
                    {
                        flag = true;
                        break;
                    }
                }
                if (flag)
                {

```

```
        continue;
    }
    yes = levDist(s, c, j, j + d - 1);
}
if (yes)
{
    dl = d;
}
else
{
    dr = d;
}
ans += sz - dl;
cout << ans;
return 0;
}
```

Task D ()

```
#include <iostream>
#include <algorithm>
#include <vector>
#include <set>
#include <map>
#include <unordered_set>
#include <unordered_map>
#include <cmath>
#include <deque>
#include <queue>
#include <list>

using namespace std;

const int INF = 1e9;

int dist(vector<vector<pair<int, int>>> &c, int ix, int iy, int jx, int jy)
{
    return abs(jx - ix - c[ix][iy].first) + abs(jy - iy - c[ix][iy].second);
}

int main()
{
    int n, m;
    cin >> n >> m;
    pair<int, int> s, f;
    cin >> s.first >> s.second >> f.first >> f.second;
    s.first--;
    s.second--;
    f.first--;
    f.second--;
    vector<vector<pair<int, int>>> c(n, vector<pair<int, int>>(m));
    for (int i = 0; i < n; ++i)
    {
        for (int j = 0; j < m; ++j)
        {
            cin >> c[i][j].first >> c[i][j].second;
        }
    }
    vector<vector<int>> d(n * m, vector<int>(n * m));
    for (int ix = 0; ix < n; ++ix)
    {
        for (int iy = 0; iy < m; ++iy)
        {
            for (int jx = 0; jx < n; ++jx)
            {
                for (int jy = 0; jy < m; ++jy)
                {
                    if (ix == jx && iy == jy)
                    {
                        continue;
                    }
                    d[ix * m + iy][jx * m + jy] = dist(c, ix, iy, jx, jy);
                }
            }
        }
    }
    for (int ix = 0; ix < n; ++ix)
    {
        for (int iy = 0; iy < m; ++iy)
        {
            for (int jx = 0; jx < n; ++jx)
            {
                for (int jy = 0; jy < m; ++jy)
                {
                    for (int kx = 0; kx < n; ++kx)
                    {
                        for (int ky = 0; ky < m; ++ky)
                        {
                            d[jx * m + jy][kx * m + ky] = min(d[jx * m
                                + jy][kx * m + ky], d[jx * m + jy][ix
                                * m + iy] + d[ix * m + iy][kx * m +
```

```
        ky]) ;  
    }  
}  
}  
}  
cout << d[s.first * m + s.second][f.first * m + f.second];  
return 0;  
}
```

Task E ()

```
#include <iostream>
#include <algorithm>
#include <vector>
#include <set>
#include <map>
#include <unordered_set>
#include <unordered_map>
#include <cmath>
#include <deque>
#include <queue>
#include <list>

using namespace std;

const long long s = 0;

int main()
{
    long long n, m, b;
    cin >> n >> m >> b;
    long long p, q;
    cin >> p >> q;
    cout << "?\u03c0" << s + p - 1 << '\u03c0' << s + q - 1 << '\u03c0' << s + 2 * n + p - 1 << '\u03c0' << s + q
        - 1 << '\n';
    fflush(stdout);
    long long k, r;
    cin >> k >> r;
    if (k == s + p - 1 && r == s + q - 1)
    {
        cout << "!?\u03c0" << s + 2 * n << '\u03c0' << s << '\n';
        fflush(stdout);
    }
    else
    {
        cout << "!?\u03c0" << s << '\u03c0' << s << '\n';
        fflush(stdout);
    }
    return 0;
}
```

Task F ()