

Олимпиада СПбГУ по информатике 2021/22 учебного года

| A | B | C | D | E | F | Sum |
|-----|-----|-----|----|----|----|-----|
| 100 | 100 | 100 | 80 | 58 | 98 | 536 |

Task A ()

```
#include <algorithm>
#include <cmath>
#include <cstring>
#include <iomanip>
#include <iostream>
#include <map>
#include <numeric>
#include <queue>
#include <set>
#include <string>
#include <unordered_map>
#include <unordered_set>
#include <vector>
#include <ctime>
#include <cassert>

#define all(a) (a).begin(), (a).end()
#define ssize(a) (int)(a).size()

using namespace std;

using ll = long long;

int main() {
#ifdef LOCAL
    freopen("input.txt", "r", stdin);
#endif
    ios_base::sync_with_stdio(false);
    cin.tie(nullptr);

    int n;
    cin >> n;
    vector<int> a(n), b(n);
    for (int i = 0; i < n; ++i) {
        cin >> a[i] >> b[i];
    }

    map<int, ll> sum;
    for (int i = 0; i < n; ++i) {
        sum[b[i]] += a[i];
    }

    for (auto &[i, j] : sum) {
        if (j % 10 != 0) {
            cout << i;
            break;
        }
        sum[i + 1] += j / 10;
    }

    return 0;
}
```

Task B ()

```
#include <algorithm>
#include <cassert>
#include <cmath>
#include <cstring>
#include <ctime>
#include <iomanip>
#include <iostream>
#include <map>
#include <numeric>
#include <queue>
#include <set>
#include <string>
#include <unordered_map>
#include <unordered_set>
#include <vector>

#define all(a) (a).begin(), (a).end()
#define ssize(a) (int)(a).size()

using namespace std;

using ll = long long;

int main() {
#ifdef LOCAL
    //freopen("input.txt", "r", stdin);
#endif
    ios_base::sync_with_stdio(false);
    cin.tie(nullptr);

    int n;
    cin >> n;
    vector<int> k(n);
    for (int i = 0; i < n; ++i) {
        cin >> k[i];
    }

    while (true) {
        int mx = n - 1;
        while (mx >= 0 && k[mx] == 0) {
            --mx;
        }
        if (mx == -1) {
            break;
        }

        cout << "Flip_and_wait" << endl;

        int cnt = 0;
        while (true) {
            string info;
            cin >> info;
            assert(info[0] == 'B');
            cnt += count(all(info), 'e') / 2;
            if (cnt >= mx + 1) {
                break;
            } else {
                cout << "Wait" << endl;
            }
        }

        --k[mx];
    }

    cout << "Stop" << endl;
}

return 0;
}
```

Task C ()

```
#include <algorithm>
#include <cassert>
#include <cmath>
#include <cstring>
#include <ctime>
#include <iomanip>
#include <iostream>
#include <map>
#include <numeric>
#include <queue>
#include <random>
#include <set>
#include <string>
#include <unordered_map>
#include <unordered_set>
#include <vector>

#define all(a) (a).begin(), (a).end()
#define ssize(a) (int)(a).size()

using namespace std;

using ll = long long;

map<string, string> f;
map<string, string> g;

void solve() {
    string s;
    cin >> s;

    int n = ssize(s);

    int cntq = count(all(s), '?');

    if (cntq == 0) {
        for (int i = 0; i + 1 < n; i += 2) {
            string tmp = f[s.substr(i, 2)];
            s[i] = tmp[0];
            s[i + 1] = tmp[1];
        }
    } else {
        for (int i = 0; i + 1 < n; i += 2) {
            string tmp = g[s.substr(i, 2)];
            s[i] = tmp[0];
            s[i + 1] = tmp[1];
        }
    }
    cout << s << "\n";
}

int main() {
#ifdef LOCAL
    freopen("input.txt", "r", stdin);
#endif
    ios_base::sync_with_stdio(false);
    cin.tie(nullptr);

    f = {{"00", "0?"}, {"01", "?1"}, {"10", "?0"}, {"11", "1?"}};
    for (auto &[x, y] : f) {
        g[y] = x;
    }

    int t;
    cin >> t;
    while (t--) {
        solve();
    }
}
```

```
    return 0;  
}
```

Task D ()

```
#include <algorithm>
#include <cassert>
#include <cmath>
#include <cstring>
#include <ctime>
#include <iomanip>
#include <iostream>
#include <map>
#include <numeric>
#include <queue>
#include <set>
#include <string>
#include <unordered_map>
#include <unordered_set>
#include <vector>

#define all(a) (a).begin(), (a).end()
#define ssize(a) (int)(a).size()

using namespace std;

using ll = long long;

const ll mod = 998244353;

map<int, int> mp{{0, 1},
{5000000, 428937595},
{10000000, 295201906},
{15000000, 813259672},
{20000000, 160030060},
{25000000, 433880730},
{30000000, 957629942},
{35000000, 31729117},
{40000000, 545208507},
{45000000, 767818091},
{50000000, 213689172},
{55000000, 363266670},
{60000000, 760025067},
{65000000, 117371703},
{70000000, 939830261},
{75000000, 770845925},
{80000000, 506268060},
{85000000, 328979964},
{90000000, 39806322},
{95000000, 512554988},
{100000000, 808258749},
{105000000, 694814243},
{110000000, 440133909},
{115000000, 385510728},
{120000000, 686156489},
{125000000, 222059821},
{130000000, 741797144},
{135000000, 677432735},
{140000000, 390377694},
{145000000, 339045014},
{150000000, 12629586},
{155000000, 634938288},
{160000000, 544711799},
{165000000, 377929821},
{170000000, 104121967},
{175000000, 313632531},
{180000000, 495867250},
{185000000, 865854329},
{190000000, 421290700},
{195000000, 386147469},
{200000000, 117153405},
{205000000, 18536028},
{210000000, 57084755},
{215000000, 325341339},
{220000000, 202713771},
{225000000, 546969497},
{230000000, 675932866},
```

{235000000, 759880589},
{240000000, 79781699},
{245000000, 848259019},
{250000000, 956276337},
{255000000, 941778993},
{260000000, 652678397},
{265000000, 315094878},
{270000000, 35212756},
{275000000, 433186147},
{280000000, 655645460},
{285000000, 64748124},
{290000000, 468129309},
{295000000, 281295633},
{300000000, 761699708},
{305000000, 600130702},
{310000000, 533047427},
{315000000, 676886948},
{320000000, 287671032},
{325000000, 423996017},
{330000000, 206068022},
{335000000, 882517476},
{340000000, 50865043},
{345000000, 993580422},
{350000000, 144980423},
{355000000, 843705280},
{360000000, 111276893},
{365000000, 26368504},
{370000000, 259415897},
{375000000, 918048438},
{380000000, 444094191},
{385000000, 723617861},
{390000000, 593907889},
{395000000, 173350007},
{400000000, 573994984},
{405000000, 401920943},
{410000000, 892454686},
{415000000, 84924870},
{420000000, 566073550},
{425000000, 874007723},
{430000000, 128761001},
{435000000, 149123648},
{440000000, 888483202},
{445000000, 855479832},
{450000000, 251718753},
{455000000, 659478190},
{460000000, 548033568},
{465000000, 93829695},
{470000000, 428105027},
{475000000, 616996159},
{480000000, 742756734},
{485000000, 633125919},
{490000000, 546182474},
{495000000, 249619035},
{500000000, 62402409},
{505000000, 514588945},
{510000000, 102052166},
{515000000, 962390239},
{520000000, 826426395},
{525000000, 687413213},
{530000000, 159186619},
{535000000, 820097297},
{540000000, 926316039},
{545000000, 850407126},
{550000000, 176055335},
{555000000, 888573766},
{560000000, 51568171},
{565000000, 341370469},
{570000000, 414163604},
{575000000, 600191572},
{580000000, 604947226},
{585000000, 632441623},
{590000000, 681666415},
{595000000, 978860867},
{600000000, 511621808},

{605000000, 631078482},
{610000000, 924112080},
{615000000, 805963889},
{620000000, 265769800},
{625000000, 172922144},
{630000000, 955559118},
{635000000, 576699812},
{640000000, 763148293},
{645000000, 253151120},
{650000000, 472709375},
{655000000, 184639537},
{660000000, 19536133},
{665000000, 687419227},
{670000000, 860830935},
{675000000, 202133852},
{680000000, 290471030},
{685000000, 422332597},
{690000000, 851685235},
{695000000, 84257200},
{700000000, 242726978},
{705000000, 744816299},
{710000000, 169855231},
{715000000, 714502830},
{720000000, 612759169},
{725000000, 158013406},
{730000000, 599797734},
{735000000, 10958310},
{740000000, 961628039},
{745000000, 261743865},
{750000000, 953297493},
{755000000, 539880795},
{760000000, 62806842},
{765000000, 681051568},
{770000000, 37844313},
{775000000, 682765157},
{780000000, 909741023},
{785000000, 551621442},
{790000000, 689361523},
{795000000, 349960501},
{800000000, 887890124},
{805000000, 568925901},
{810000000, 380694152},
{815000000, 109618190},
{820000000, 669317759},
{825000000, 918239352},
{830000000, 367270918},
{835000000, 899305835},
{840000000, 806951470},
{845000000, 664034750},
{850000000, 843736533},
{855000000, 776142608},
{860000000, 377403437},
{865000000, 354033051},
{870000000, 945260111},
{875000000, 239480646},
{880000000, 786127243},
{885000000, 12198440},
{890000000, 80918046},
{895000000, 49743354},
{900000000, 875880304},
{905000000, 636257427},
{910000000, 364983542},
{915000000, 994704486},
{920000000, 623250998},
{925000000, 68064804},
{930000000, 598764068},
{935000000, 278395191},
{940000000, 804930040},
{945000000, 756464212},
{950000000, 24257676},
{955000000, 971716517},
{960000000, 214821357},
{965000000, 707669156},
{970000000, 791011898},

```

{975000000, 291032164},
{980000000, 954947696},
{985000000, 289232396},
{990000000, 183092975},
{995000000, 781587414},
};

11 fact(11 n) {
    auto it = __mp.upper_bound(n);
    11 ans = it->second;
    for (int i = it->first + 1; i <= n; ++i) {
        ans = ans * i % mod;
    }
    return ans;
}

11 binpow(11 a, 11 p) {
    if (p == 0) {
        return 1;
    }
    if (p % 2 == 0) {
        return binpow(a * a % mod, p / 2);
    }
    return a * binpow(a, p - 1) % mod;
}

int main() {
#ifdef LOCAL
    freopen("input.txt", "r", stdin);
#endif
    ios_base::sync_with_stdio(false);
    cin.tie(nullptr);

    11 n;
    cin >> n;

    n += 1;

    11 rest = n % mod;
    11 ans = fact(rest);

    11 k = n / mod;

    if (n >= mod * mod) {
        ++k;
        ans = ans * (mod - 1) % mod;
        ans = ans * fact(n / mod - mod) % mod;
    } else {
        ans = ans * fact(k) % mod;
    }

    ans = ans * binpow(mod - 1, k) % mod;

    cout << k << " " << ans;

    return 0;
}

```

Task E ()

```
#pragma GCC optimize("O3")

#include <algorithm>
#include <cassert>
#include <cmath>
#include <cstring>
#include <ctime>
#include <iomanip>
#include <iostream>
#include <map>
#include <numeric>
#include <queue>
#include <set>
#include <string>
#include <unordered_map>
#include <unordered_set>
#include <vector>

#define all(a) (a).begin(), (a).end()
#define ssize(a) (int)(a).size()

using namespace std;

using ll = long long;

const int max_n = 3e5 + 5;

int tree[max_n];
void update(int pos, int dlt) {
    for (int i = pos; i < max_n; i = i | (i + 1)) {
        tree[i] += dlt;
    }
}

int get(int r) {
    int res = 0;
    for (int i = r; i >= 0; i = (i & (i + 1)) - 1) {
        res += tree[i];
    }
    return res;
}

int get(int l, int r) { return get(r) - get(l - 1); }

struct Query {
    int l;
    int r;
    int d;
    int id;
};

bool operator<(const Query &lhs, const Query &rhs) {
    int bl = lhs.l >> 8;
    int br = rhs.l >> 8;
    if (bl == br) {
        if (bl & 1) {
            return lhs.r > rhs.r;
        }
        return lhs.r < rhs.r;
    }
    return bl < br;
}

int ceil_div(int a, int b) { return (a + b - 1) / b; }

int a[max_n];

int main() {
#ifdef LOCAL
    freopen("input.txt", "r", stdin);
#endif
}
```

```

ios_base::sync_with_stdio(false);
cin.tie(nullptr);

int n;
cin >> n;
for (int i = 0; i < n; ++i) {
    cin >> a[i];
}

int q;
cin >> q;

vector<Query> queries(q);

for (int i = 0; i < q; ++i) {
    cin >> queries[i].l >> queries[i].r >> queries[i].d;
    --queries[i].r;
    queries[i].id = i;
}

sort(all(queries));

vector<ll> ans(q);

int l = 0;
int r = -1;

for (auto &el : queries) {
    while (l > el.l) {
        --l;
        update(a[l], 1);
    }
    while (r < el.r) {
        ++r;
        update(a[r], 1);
    }
    while (l < el.l) {
        update(a[l], -1);
        ++l;
    }
    while (r > el.r) {
        update(a[r], -1);
        --r;
    }
}

int pref_cnt = 0;

for (int i = 1; i <= el.d && i < max_n;) {
    int j = ceil_div(el.d, i);
    int next_i;
    if (j == 1) {
        next_i = max_n;
    } else {
        next_i = ceil_div(el.d, j - 1);
    }

    //cout << i << " " << next_i << " " << j << "\n";

    int ask_r = min(next_i - 1, max_n - 1);

    int new_pref_cnt = get(ask_r);
    int cnt = new_pref_cnt - pref_cnt;
    pref_cnt = new_pref_cnt;

    ans[el.id] += (ll)j * cnt;

    i = next_i;
}

for (int i = 0; i < q; ++i) {
    cout << ans[i] << "\n";
}

```

```
    return 0;  
}
```

Task F ()

```
#include <algorithm>
#include <cassert>
#include <cmath>
#include <cstring>
#include <ctime>
#include <iomanip>
#include <iostream>
#include <map>
#include <numeric>
#include <queue>
#include <set>
#include <string>
#include <unordered_map>
#include <unordered_set>
#include <vector>

#define all(a) (a).begin(), (a).end()
#define ssize(a) (int)(a).size()

using namespace std;

using ll = long long;

void compress(vector<ll>& a) {
    vector<ll> vals = a;
    sort(all(vals));
    vals.resize(unique(all(vals)) - vals.begin());
    for (auto &x : a) {
        x = lower_bound(all(vals), x) - vals.begin();
    }
}

struct BIT {
    vector<int> tree;
    BIT() {}
    BIT(int n) {
        tree.resize(n);
    }
    void update(int pos, int val) {
        for (int i = pos; i < ssize(tree); i = i | (i + 1)) {
            tree[i] = max(tree[i], val);
        }
    }
    int get(int r) {
        int res = 0;
        for (int i = r; i >= 0; i = (i & (i + 1)) - 1) {
            res = max(res, tree[i]);
        }
        return res;
    }
};

vector<BIT> tree;
vector<vector<int>> vals;

void update(int pos, int x, int y) {
    for (int i = pos; i >= 0; i = (i & (i + 1)) - 1) {
        int pos = lower_bound(all(vals[i]), x) - vals[i].begin();
        tree[i].update(pos, y);
    }
}

int get(int lx, int ry) {
    int res = 0;
    for (int i = lx; i < ssize(tree); i = i | (i + 1)) {
        int pos = upper_bound(all(vals[i]), ry) - vals[i].begin() - 1;
```

```

        if (pos >= 0) {
            res = max(res, tree[i].get(pos));
        }
    }
    return res;
}

int main() {
#ifndef LOCAL
    freopen("input.txt", "r", stdin);
#endif
    ios_base::sync_with_stdio(false);
    cin.tie(nullptr);

    int n;
    cin >> n;
    ++n;
    vector<int> l(n), r(n);
    for (int i = 1; i < n; ++i) {
        cin >> l[i] >> r[i];
    }

    vector<ll> pref_l(n), pref_r(n);
    for (int i = 1; i < n; ++i) {
        pref_l[i] = pref_l[i - 1] + l[i];
        pref_r[i] = pref_r[i - 1] + r[i];
    }

    compress(pref_l);
    compress(pref_r);

    tree.resize(ssize(pref_l));
    vals.resize(ssize(pref_l));

    for (int i = 0; i < n; ++i) {
        for (int j = pref_l[i]; j >= 0; j = (j & (j + 1)) - 1) {
            vals[j].push_back(pref_r[i]);
        }
        for (int i = 0; i < n; ++i) {
            sort(all(vals[i]));
            vals[i].resize(unique(all(vals[i])) - vals[i].begin());
            tree[i] = BIT(ssize(vals[i]));
        }
    }

    vector<int> dp(n);

    for (int i = 0; i < n; ++i) {
        int max_prev = get(pref_l[i], pref_r[i]);
        dp[i] = max_prev + 1;
        update(pref_l[i], pref_r[i], dp[i]);
    }

    int ans = *max_element(all(dp));
    cout << ans;
}

return 0;
}

```